

RIDEX PLUS



TRANSMISSION FLUIDS CATALOGUE

RIDEX is a German-based automotive aftermarket company established in 2016. In just 9 years, we have sold over 45 million items to more than 10.1 million customers in 27 European countries.

The RIDEX portfolio has over 480 product categories that include more than 58,000 articles produced at certified factories in Europe and Asia under three brands – RIDEX, RIDEX PLUS, and RIDEX REMAN.

95,000+ m²

warehouse space*

58,000+

references available

10,100,000+

customers

*Total space in AUTODOC's warehouse facilities

SOLD IN
27
EUROPEAN
COUNTRIES



Everything you need

From basic to advanced, from sustainability to performance – we've got the right products for every individual need.



Quality guaranteed

Laboratory-tested parts from certified factories only.



Excellent price

Great prices on reliable products certified according to international standards.



Dedicated service

Your personal account manager and the customer support team are always there.



THE RIGHT TRANSMISSION FLUID FOR EVERY NEED

Premium ATFs & MTFs for peak performance

PACKING



MAXIMUM PROTECTION, ZERO LEAKS

Ensures a tight seal to prevent leakage and protect against contaminants

ERGONOMIC PACKAGING

Modern, lightweight, and easy-to-handle packaging

CLEAR PRODUCT IDENTIFICATION

Product name

Product specifications

Product volume: 1L

COMPACT DESIGN

The product occupies less space on garage and warehouse shelves



CLEAR & PRACTICAL LABELLING

ATFs and MTFs are easily identifiable by the font colour and an image of a transmission



AUTOMATIC TRANSMISSION FLUIDS

Our ATFs are engineered to deliver superior performance and reliability across a wide range of vehicles. They are specifically designed to ensure smooth gear shifts, enhance hydraulic system functionality, and extend the life of your transmission. Whether you need a mineral or fully synthetic ATF, we provide solutions tailored to meet the demands of most automatic transmission, power steering, and other hydraulic systems in passenger cars and trucks.

ATF 6HP

Art. No: 3069A0028P



Performance specifications

- AML: 4G4319A509/AA/S
- BENTLEY: PY112995PA
- BMW: 83220142516
- BMW: M-1375.4
- HYUNDAI: 040000C90SG
- JAGUAR: Fluid 8432
- LAND ROVER: TYK500050
- MASERATI: 231603
- VW: G 055 005
- ZF: TE-ML 11

Description

This full synthetic fluid formulated with carefully selected high-quality base oils has been specifically developed for ZF 6-speed automatic transmissions. Its unique formula ensures trouble-free operation and smooth gear shifting.



6 SPEED

Applications

Mainly designed for ZF 6-speed automatic transmissions, such as those installed in BMW, Jaguar, and Land Rover vehicles. It is also suitable for other manufacturers who recommend this type of oil (e.g. Audi Quattro).

Base oil type

Full synthetic

Characteristics

	Unit	Average Value
Density at 15°C	kg/l	0.845
Viscosity at 40°C	mm ² /s	31.0
Viscosity at 100°C	mm ² /s	6.2
Brookfield viscosity at -40°C	mPa·s	9,500
Viscosity index	—	153
Flash point COC	°C	202
Pour point	°C	-48
Colour	—	Yellow-brown

Packaging



12×1L

The data mentioned in this product information sheet is intended to enable the reader to understand the properties and potential applications of our products. We reserve the right to modify the general characteristics of our products in order to offer our customers the latest technical developments. You can download the most recent material safety data sheet for this product from our website.

ATF 8HP

Art. No: 3069A0035P



Performance specifications

- ZF 8 HP
- BMW: 83222152426
- CHRYSLER: 68157995AA
- FIAT: 9.55550-AV5
- JAGUAR: 02JDE26444
- LAND ROVER: LR023288
- VW 060 162

Description

This full synthetic fluid is formulated with exceptionally high-quality base oils that have been carefully selected. It has been specifically developed for ZF 6-, 8-, and 9-speed automatic transmissions. The unique formula ensures trouble-free operation and smooth gear shifting.



8 SPEED

Applications

ZF 6-, 8-, and 9-speed automatic transmissions.

Base oil type

Full synthetic

Characteristics

	Unit	Average Value
Density at 15°C	kg/l	0.845
Viscosity at 40°C	mm ² /s	28.1
Viscosity at 100°C	mm ² /s	5.94
Brookfield viscosity at -40°C	mPa·s	9,500
Viscosity index	—	164
Flash point COC	°C	210
Pour point	°C	-48
Colour	—	Yellow-brown

Packaging



12×1L

The data mentioned in this product information sheet is intended to enable the reader to understand the properties and potential applications of our products. We reserve the right to modify the general characteristics of our products in order to offer our customers the latest technical developments. You can download the most recent material safety data sheet for this product from our website.

ATF CVT

Art. No: 3069A0014P



Performance specifications

- Chrysler/Dodge/Jeep NS-2 / Mopar CVTF+4
- Daihatsu Amix CVTF DC / DFC / DFE
- Ford WSS-M2C928-A / Hybrid e-CVT
- GM DEX-CVT / 1940713 / 1940714
- Honda HMMF (without starting clutch) / HCF2 / HEVF
- Hyundai/Kia CVT-1 / SP III (CVT model)
- Jatco CVT 8 Hybrid
- Mazda JWS 3320
- MB 236.20
- Mitsubishi SP-III (only CVT) / CVTF J1/(ECO)J4/J4+
- Mini Cooper EZL 799 / 799A
- Nissan NS-1/2/2V/3 / N-CVT
- Subaru ECVT / iCVT / iCVT FG / CVT-LV / NS-2
- Subaru Lineartronic High Torque (HT) CVTF
- Subaru Lineartronic chain CVTF / CVTF II/III
- Suzuki CVTF TC / 3320 / 4401 / NS-2 / Green 1/2/1V
- Toyota CVTF TC / FE / THSII
- VW G 052 180 / G 052 516

Description

This full synthetic fluid is formulated with exceptionally high- quality base oils that have been carefully selected. It has been designed to be compatible with most CVT gearboxes. It is suitable for continuously variable transmissions featuring steel push belts or chains. The product offers outstanding anti-wear protection and stable friction characteristics.



CVT

Applications

OEMs usually recommend specific CVT fluids for their transmissions. By carefully balancing base oils and advanced additives, the formula meets the requirements of both European and Japanese CVT manufacturers. This product may not be suitable for use in some hybrid vehicles as they require specialised fluids.

Base oil type

Full synthetic

Characteristics

	Unit	Average Value
Density at 15°C	kg/l	0.852
Viscosity at 40°C	mm ² /s	34.2
Viscosity at 100°C	mm ² /s	7.35
Brookfield viscosity at -40°C	mPa·s	10,600
Viscosity index	—	189
Flash point COC	°C	210

Packaging



12×1L

The data mentioned in this product information sheet is intended to enable the reader to understand the properties and potential applications of our products. We reserve the right to modify the general characteristics of our products in order to offer our customers the latest technical developments. You can download the most recent material safety data sheet for this product from our website.



Performance specifications

- BMW DCTF-1 / 1+
- BMW DCTF-2
- BMW MTF LT-5
- BorgWarner
- Bugatti Veyron
- Chrysler 68044345 EA & GA
- DTFR 13C130
- Ferrari TF DCT-F3
- FIAT 9.55550-DA11
- FIAT 9.55550-HE2
- FIAT 9.55550-MZ6
- Ford WSS-M2C936-A
- Ford WSS-M2C218-A1
- Ford WSS-M2C200-D2
- Hyundai/Kia
- MB 236.21 / 236.22 / 236.24 / 236.25 / 239.21
- Mitsubishi Dia-Queen SSTF-1
- Nissan 999MP-6 TR T00P
- Nissan GT-R R35 Special
- Porsche 000.043.20
- Porsche 000.043.207.29
- Porsche 000.043.207.30
- Porsche 999.917.080.01
- Porsche/ZF FFL-3
- PSA 9734 S2
- Renault EDC / DC4 / DW5 / DW6
- Renault BOT450 EDC 6-Speed
- Toyota JWS 2271
- Volvo BOT341 #1161838 / 1161839 / D1 / D2
- VW G 052 182
- VW G 052 513
- VW G 052 529 / VW G 055 529
- VW G 052 536 / VW G 055 536
- VW G 060 726
- VW G 070 726
- VW TL 52182

Description

This full synthetic lubricant is formulated with high-quality base oils that have been carefully selected. It has been specifically developed for dual clutch transmissions (DCT) in modern passenger cars. It ensures that these transmissions operate trouble-free.



DSG

Applications

Mainly designed for VAG direct shift gearboxes (DSG), this fluid can also be used for other 6-speed DCT transmissions, such as the Chrysler Powershift, Ford Powershift, Mitsubishi TC-SST, Volvo Powershift, and BMW Drivelogic 7-speed. This product is not suitable for the VW dry clutch DSG type 0AM, 02M, 02Q, and 02S.

Base oil type

Full synthetic

Characteristics

	Unit	Average Value
Density at 15°C	kg/l	0.854
Viscosity at 40°C	mm ² /s	34.00
Viscosity at 100°C	mm ² /s	7.0
Viscosity index	—	173
Flash point COC	°C	201
Pour point	°C	-48

Packaging



12×1L

The data mentioned in this product information sheet is intended to enable the reader to understand the properties and potential applications of our products. We reserve the right to modify the general characteristics of our products in order to offer our customers the latest technical developments. You can download the most recent material safety data sheet for this product from our website.

ATF II

Art. No: 3069A0011P



Performance specifications

- ALLISON : C4
- CATERPILLAR: TO-2
- DTFR 13C140
- FORD Mercon: M2C-138CJ / 166-H
- GM: 6137-M DEXRON II-D
- MAN: 339 V1/Z1
- MB: 236.1
- MB: 236.5
- MB: 236.7
- VOITH: H55.6335 (G607)
- ZF: TE-ML 03D
- ZF: TE-ML 04D
- ZF: TE-ML 09
- ZF: TE-ML 11A
- ZF: TE-ML 14A
- ZF: TE-ML 17C

Description

This fluid has a high viscosity index and is made specifically for automatic transmissions. It offers high chemical stability, increased anti-wear properties, and excellent resistance against ageing.



**DEXTRON
II D**

Applications

This fluid can be used in automatic transmissions, torque converters, power steering systems, and hydraulic circuits which require a product that meets the General Motors ATF TYPE Dexron II-D requirements.

Base oil type

Mineral

Characteristics

	Unit	Average Value
Density at 15°C	kg/l	0.867
Viscosity at 40°C	mm ² /s	37.40
Viscosity at 100°C	mm ² /s	7.46
Viscosity index	—	171
Flash point COC	°C	198
Pour point	°C	-48
Total base number	mgKOH/g	2.4

Packaging



12×1L

The data mentioned in this product information sheet is intended to enable the reader to understand the properties and potential applications of our products. We reserve the right to modify the general characteristics of our products in order to offer our customers the latest technical developments. You can download the most recent material safety data sheet for this product from our website.



Performance specifications

- Dexron IID/IIIE/IIIF/IIIG/IIIH
- DTFR 13C100 / 13C140 / 13C170
- MB 236.1/236.5/236.6/236.7/236.9
- Ford Mercon/M2C138-CJ
- Ford ESP M2C166-H
- MAN 339 Typ Z1/V1
- Allison C4/TES-389
- Cat TO-2
- Voith 55.6335 (G607)
- Volvo 97341
- ZF TE-ML 02F/03D/04D/09A/09B/11A/11B/14A/17C

Description

This is a mineral fluid formulated with highly refined base oils that have been carefully selected. This oil has a very high viscosity index, developed for most automatic transmissions. The improved fluidity at low temperatures ensures optimum performance in all conditions. Its exceptional frictional characteristics provide smooth gear shifting and driving comfort.



**DEXTRON
III H**

Applications

This fluid is used in automatic transmissions, torque converters, power steering systems, and hydraulic circuits which require a product that meets the General Motors ATF TYPE Dexron III or Dexron II E and Ford Mercon requirements.

Base oil type

Mineral

Characteristics

	Unit	Average Value
Density at 15°C	kg/l	0.855
Viscosity at 40°C	mm ² /s	33.9
Viscosity at 100°C	mm ² /s	7.1
Brookfield viscosity at -40°C	mPa·s	17,500
Viscosity index	—	179
Flash point COC	°C	196
Pour point	°C	-45
Colour	—	Red

Packaging



12×1L

The data mentioned in this product information sheet is intended to enable the reader to understand the properties and potential applications of our products. We reserve the right to modify the general characteristics of our products in order to offer our customers the latest technical developments. You can download the most recent material safety data sheet for this product from our website.

ATF VI

Art. No: 3069A0002P



Performance specifications

- AisinWarner JWS 3309(T-IV)/3324(WS)/AW-1/AW-2
- Allison C3/C4 / TES-389/468, ATF RED-1K
- BMW ATF 2/3+6/7 / 7045E/8072B/LA2634/ATF6/Mini/LT71141
- Cat TO-2
- Chrysler Dodge Mopar AS68RC/69RC (T-IV)
- Chrysler ATF+ / +2 / +3
- Daihatsu ATF D-II/D-III SP
- DTFR 13C100 / 120 / 140 / 150 / 170 / 38B100
- Fiat Type IV / 9.55550-AV5/AV6
- Ford Mercon LV/Mercon/M2C138-CJ/166-H/922-A1/924-A/938-A
- GM Dexron VI/II/IID/IIIE/IIIG/IIIH, TASA
- Honda Acura / ATF 3.0/3.1/DW-1/ATF-Z1(except in CVT)
- Hyundai/Kia SP-II/SP-III/SP-IV/SP-IV M/SP-IV RR
- Hyundai/Kia JWS 3314/9683, Isuzu ATF II/III/SP
- Jaguar ATF 3403 M115/JLM 20238/20292
- JASO M315-2013 1A/1A-LV/2A
- Mazda ATF DII/M-III/M-V/FZ/F-1/S-1/N-1/3317
- MB 236.1/2/3/236.5/236.7/236.8/236.9/236.41
- Mitsubishi SK/SP-II/SP-III/SP-IV/AW/J2/J3/PA/MA1
- Nissan Matic C/D/J/K/P/S/W
- Porsche 3403-M115/T-IV
- Subaru ATF ATF/AW-1/5AT/ATF HP
- Suzuki ATF 3309/3314/3317/2326/2384K
- PSA B71 2340
- Toyota D-II/D-III/T-III/T-IV/WS
- VW G 052 025 / G 052 055 / G 052 162 / G 052 990
- VW G 053 001 / G 053 025 / G 055 005 / G 055 025
- VW G 055 162 / G 055 540 / G 060 162
- VOITH 55.6335.xx (G607)
- VOLVO 97335/97340/1161540
- ZF 3-/4-/6-/8-/9-SPEED
- ZF 5HP 18FL/19FL/24A/30/4HP20
- ML05L/09/11A/B/21L

Description

This is a full synthetic fluid formulated with carefully selected high-quality base oils, meeting the requirements of the General Motors Dexron VI specification. Its special composition allows it to be used in all applications where the older Dexron II and Dexron III fluids are recommended.



DEXTRON VI

Applications

This high-quality ATF can be used in passenger car automatic transmissions with torque converters, as well as in wet clutches and power steering units.

Base oil type

Full synthetic

Characteristics

	Unit	Average Value
Density at 15°C	kg/l	0.847
Viscosity at 40°C	mm ² /s	30
Viscosity at 100°C	mm ² /s	6.0
Brookfield viscosity at -40°C	mPa·s	12,000
Viscosity index	—	151
Colour	—	Red

Packaging



12×1L

The data mentioned in this product information sheet is intended to enable the reader to understand the properties and potential applications of our products. We reserve the right to modify the general characteristics of our products in order to offer our customers the latest technical developments. You can download the most recent material safety data sheet for this product from our website.



Performance specifications

- AISIN-WARNER: JWS 3309 / 3314 / 3317 / AW
- ALLISON C4 / TES 295 / TES-389
- BMW: ETL 7045E
- BMW: ETL 8072B
- BMW: LA 2634
- BMW: LT 71141
- CHRYSLER: ATF +3 AND +4
- DTFR 13C100 / 110 / 120 / 140 / 160 / 170 / 38B100
- FIAT: 9.55550-AV4
- FORD: MERCON V / XL-12
- FORD: WSS-M2C922-A1
- GM: DEXRON III-H, IIG & IID
- HONDA: ATF Z-1 / DW-1
- HYUNDAI / KIA JWS 3314 / NWS 9638
- HYUNDAI / KIA: SP-II / SP-III / SP-IV / SP-IV M/ SP-IV RR
- JASO 1-A
- MAN 339 Type L1/V2/Z2
- MAZDA ATF M-III / M-V
- MB 236.1 / 236.2 / 236.3 / 236.5 / 236.6 / 236.7 / 236.9 / 236.10
- MB 236.11 / 236.12 / 236.14 / 236.15 / 236.81 / 236.93
- MITSUBISHI SP-II / SP-III / SP-IV / J2 / J3
- NISSAN MATIC D/J/K/S/W
- SUBARU ATF /HP
- SUZUKI 3314 / 3317
- TOYOTA T / T-II / T-III / T-IV
- VOITH 55.6336
- VOLVO 97940 / 97341
- VW G 052 162 / 052 990 / 055 005 / 055 025
- VW G 055 162 / 055 540
- ZF TE-ML 04D / 05L / 09 / 11A / 11B / 14B / 16L / 20B

Description

This fully synthetic fluid is formulated with highly refined base oils that have been carefully selected for automatic transmissions, meeting the requirements of most American, Japanese, and European manufacturers.



Applications

The product's versatility ensures it can be used in the automatic transmissions and torque converters of most passenger cars, off-road vehicles, and SUVs.

Base oil type

Full synthetic

Characteristics

	Unit	Average Value
Density at 15°C	kg/l	0.849
Viscosity at 40°C	mm ² /s	32.7
Viscosity at 100°C	mm ² /s	7.02
Brookfield viscosity at -40°C	mPa·s	12,000
Viscosity index	—	184
Flash point COC	°C	218
Pour point	°C	-48
Colour	—	Red

Packaging



12×1L

The data mentioned in this product information sheet is intended to enable the reader to understand the properties and potential applications of our products. We reserve the right to modify the general characteristics of our products in order to offer our customers the latest technical developments. You can download the most recent material safety data sheet for this product from our website.



MANUAL TRANSMISSION FLUIDS

Our MTFs are carefully developed to provide unmatched durability and protection for gearboxes, steering boxes, and differentials. Available in mineral, semi-synthetic, and full synthetic formulas, the products ensure optimal performance under high pressure, as well as in extreme temperature conditions. These oils reduce wear, minimise friction, and enhance the longevity of the transmission components, making them an ideal choice for passenger cars and heavy-duty vehicles.

MTF 75W-80 GL-4

Art. No: 1667T0004P



Performance specifications

- API: GL-4
- BMW MTF LT-2 / LT-3 / LT-4
- FIAT: MZ1 / MZ6 / MZ7
- FORD: WSD-M2C200-C
- FORD: WSD-M2C200-D2
- FORD: ESD-M2C186-A
- GM: GMW16612 / 1940004 / 19259104
- GM: 1940182 / 1940764 / 1940768
- HONDA: MTF / MTF-II / MTF-III
- MB: 235.10
- NISSAN: MT-XZ / MT-XZ TL (JR Type)
- PSA: B71 2330
- Special gear oil, MTF 94
- Tranself NFJ / NFP / TRJ / TRP / TRT / TRX / TRZ
- VOLVO: 97308 / 97309
- VW G 009 317 / G 052 171 / G 052 178
- VW G 052 512 / G 055 512 / G 052 527 / G 052 726
- VW G 060 726 / G 070 726 / G 50

Description

This is a high-quality transmission oil, suitable for nearly all manual gearboxes in passenger cars. It is especially suitable as a replacement for specific OEM oils, simplifying gearbox oil storage. Tested under strict conditions, this oil fulfills the general performance requirements of most car makes and models in all weather conditions.



Applications

This product meets the general performance requirements of most brands and models in all weather conditions.

Base oil type

Semi-synthetic

Characteristics

	Unit	Average Value
Density at 15°C	kg/l	0.872
Viscosity at 40°C	mm ² /s	45.8
Viscosity at 100°C	mm ² /s	9.1
Brookfield viscosity at -40°C	mPa·s	142,000
Viscosity index	—	185
Flash point COC	°C	205
Pour point	°C	-45

Packaging



12×1L

The data mentioned in this product information sheet is intended to enable the reader to understand the properties and potential applications of our products. We reserve the right to modify the general characteristics of our products in order to offer our customers the latest technical developments. You can download the most recent material safety data sheet for this product from our website.

MTF 75W-80 GL-5

Art. No: 1667T0007P



Performance specifications

- API GL5
- ZF TE-ML 02B, 05B, 07A, 17B, 19C, 21B
- VOITH 3.325-340
- MB: 235.11
- MACK:GO-J
- MAN: 341 Z2, 341 E3, 342 M3
- FIAT DUCATO
- ROVER

Description

This gear oil is a semi-synthetic lubricating oil for manual transmissions, formulated with high-quality refined and synthetic base oils, as well as special EP additives to obtain the following properties:

- Excellent resistance against oxidation
- High resistance against wear, corrosion, and foaming
- A low pour point
- Exceptional EP-properties
- Fuel economy



Applications

This gear oil is used in hypoid differentials under very high stress conditions and can be used in transmissions that require EP transmission oils.

Base oil type

Semi-synthetic

Characteristics

	Unit	Average Value
Density at 15°C	kg/l	0.880
Viscosity at 40°C	mm ² /s	49.6
Viscosity at 100°C	mm ² /s	9.23
Brookfield viscosity at -40°C	mPa·s	65,000
Viscosity index	—	171
Pour point	°C	-45

Packaging



12×1L

The data mentioned in this product information sheet is intended to enable the reader to understand the properties and potential applications of our products. We reserve the right to modify the general characteristics of our products in order to offer our customers the latest technical developments. You can download the most recent material safety data sheet for this product from our website.

MTF 75W-90 GL-4/GL-5

Art. No: 1667T0002P



Performance specifications

- API: GL-4
- API: GL-5
- API: MT-1
- DAF: GL5
- IVECO: VOITH 3.325-340
- MACK: GO-J EO-H
- MAN: 341 E-3
- MAN: 341 Z-2
- MAN: 342 M-3
- MAN: 3343-SL
- MAN: 342 S1
- MAN: 342 SL
- MB: 235.6/235.8
- MIL: PRF-2105E
- RENAULT: B0032/3 Annex 3
- SAE: J 2360
- SCANIA: STO 1
- VOLVO: 97312
- ZF: TE-ML 02B
- ZF: TE-ML 05B
- ZF: TE-ML 07A
- ZF: TE-ML 08
- ZF: TE-ML 12B
- ZF: TE-ML 12L
- ZF: TE-ML 12N
- ZF: TE-ML 16F
- ZF: TE-ML 17B
- ZF: TE-ML 19C
- ZF: TE-ML 21B
- TMS 6816
- DIN 51517

Description

This full synthetic lubricant is formulated with carefully selected high-quality base oils and can be used in a wide range of applications. Due to its special composition, it is particularly suited for synchronised gear boxes, as well as heavily loaded differentials.



Applications

This oil is recommended for all the components of mechanical transmissions (gear boxes, transfer cases, differentials, etc.) in trucks and four-wheel drive vehicles.

Base oil type

Full synthetic

Characteristics

	Unit	Average Value
Density at 15°C	kg/l	0.869
Viscosity at 40°C	mm ² /s	101.00
Viscosity at 100°C	mm ² /s	15.40
Viscosity index	—	150
Flash point COC	°C	218
Pour point	°C	-40
Total base number	mgKOH/g	2.1

Packaging



12×1L

The data mentioned in this product information sheet is intended to enable the reader to understand the properties and potential applications of our products. We reserve the right to modify the general characteristics of our products in order to offer our customers the latest technical developments. You can download the most recent material safety data sheet for this product from our website.

MTF 75W-90 GL-5

Art. No: 1667T0005P



Performance specifications

- API: GL-5
- MT-1
- SCANIA: STO 1.0
- SAE: J2360
- ZF TE-ML 02B, 05B, 07A, 08, 12B, 16F, 17B, 19C, 21B
- MB 235.8
- MACK GO-J
- MAN 341Z2, 341 E3, 342 M3
- IVECO AXLES
- VOITH 3.325-340
- MIL-L-2105E
- ARVIN MERITOR O-76N
- TMS-6816
- PERFECT CORRECT GL-4

Description

This gear oil is a semi-synthetic lubricating oil for manual transmissions, formulated with high-quality refined and synthetic base oils, as well as special EP additives to obtain the following properties:

- Excellent resistance against oxidation
- High resistance against wear, corrosion, and foaming
- A low pour point
- Exceptional EP-properties
- Fuel economy



Applications

This gear oil is used in hypoid differentials under very high stress conditions and can be used in transmissions that require EP transmission oils.

Base oil type

Semi-synthetic

Characteristics

	Unit	Average Value
Density at 15°C	kg/l	0.861
Viscosity at 40°C	mm ² /s	81.00
Viscosity at 100°C	mm ² /s	15.00
Brookfield viscosity at -40°C	mPa·s	130,000
Viscosity index	—	196
Flash point COC	°C	206
Pour point	°C	-45

Packaging



12×1L

The data mentioned in this product information sheet is intended to enable the reader to understand the properties and potential applications of our products. We reserve the right to modify the general characteristics of our products in order to offer our customers the latest technical developments. You can download the most recent material safety data sheet for this product from our website.

BECOME A RIDEX DEALER

Get on the fast track to becoming a dealer. We offer a professional RIDEX website, quick search engine, convenient catalogue, secure payment, a personal account manager, and dedicated customer support to make your business with us smooth and simple.

CREATE YOUR SUCCESS STORY WITH RIDEX

1


Submit a request. An account manager will contact you via your preferred communication channel.

2

Consult your personal account manager. Your account manager will answer your questions and will give you a quote for the products in your list or select an assortment to suit your requirements.


3

Make a good deal. We'll offer you the best price for the spare parts you need and calculate the cost and delivery time for your country.



Scan the QR code and fill in the BECOME A DEALER form, or send your request to us at sales@ridex.de

ALWAYS ONLINE



OUR ADVANTAGES

- Website with great cataloguing and fast order features
- Personal customer support
- 3–5 business days for delivery to EU countries
- Wide range of reliable products
- Attractive pricing conditions for each partner *
- Marketing support for product launches

*For further information, please contact us via the request form or ask your personal account manager.

RIDEX PLUS



ATF 8HP

RIDEX PLUS
AUTOMATIC
TRANSMISSION FLUID

ZF 8HP, BMW 8322132120
FUCHS 91322132120
MANN 120 080 182
MANN 120 080 182
MANN 120 080 182
MANN 120 080 182
MANN 120 080 182
MANN 120 080 182

1L

RIDEX GmbH
Josef-Orlopp-Straße 55, 10365 Berlin, Germany

sales@ridex.de
www.ridex.eu

